



VALCAM-HT™

Obenhängender Normschieber für außermittige Druckbelastungen



Product description:

Aerial cam unit capable to withstand thrust load from all directions (right and left, up and down)
Working force designed for 1 million strokes

For more information, see the working force distribution diagram in the [PDF](#)

Article properties:

CAM-Type	Aerial CAM
----------	------------

Variants:

Articlenumber	Article name	Cam Width W1	Shutheight H1	Work Area Width W	Work Area Height H	Stroke Hw	Working Angle u (°)	Working Force F (kN)*	Weight (kg)
VACYHT100-00	VACYHT100-00	100	245	100	115	35,4	0	86,7	33,2
VACYHT100-10	VACYHT100-10	100	245	100	115	42,8	10	86,7	32,2
VACYHT100-20	VACYHT100-20	100	245	100	115	50,7	20	86,7	31,5
VACYHT100-30	VACYHT100-30	100	250	100	115	59,7	30	86,7	31,5
VACYHT100-40	VACYHT100-40	100	260	100	115	70,7	40	86,7	32
VACYHT100-50	VACYHT100-50	100	270	100	115	85,6	50	86,7	32,9
VACYHT100-60	VACYHT100-60	100	280	100	115	82	60	86,7	34,5
VACYHT100-70	VACYHT100-70	100	280	100	115	81,9	70	86,7	36,2
VACPHT100-00	VACPHT100-00	100	245	100	115	35,4	0	116,1	33,2
VACPHT100-10	VACPHT100-10	100	245	100	115	42,8	10	116,1	32,2
VACPHT100-20	VACPHT100-20	100	245	100	115	50,7	20	116,1	31,5
VACPHT100-30	VACPHT100-30	100	250	100	115	59,7	30	116,1	31,5
VACPHT100-40	VACPHT100-40	100	260	100	115	70,7	40	116,1	32
VACPHT100-50	VACPHT100-50	100	270	100	115	85,6	50	116,1	32,9
VACPHT100-60	VACPHT100-60	100	280	100	115	82	60	116,1	34,5
VACPHT100-70	VACPHT100-70	100	280	100	115	81,9	70	116,1	36,2
VACYHT140-00	VACYHT140-00	140	275	140	120	35,4	0	112,8	53
VACYHT140-10	VACYHT140-10	140	275	140	120	42,8	10	112,8	51,5
VACYHT140-20	VACYHT140-20	140	275	140	120	50,7	20	112,8	50,5
VACYHT140-30	VACYHT140-30	140	275	140	120	59,7	30	112,8	49,8
VACYHT140-40	VACYHT140-40	140	285	140	120	70,7	40	112,8	51,1
VACYHT140-50	VACYHT140-50	140	300	140	120	85,6	50	112,8	54
VACYHT140-60	VACYHT140-60	140	310	140	120	82	60	112,8	56
VACYHT140-70	VACYHT140-70	140	310	140	120	81,9	70	112,8	57,5

VALCAM-HT™

Obenhängender Normschieber für außermittige Druckbelastungen



Articlenumber	Article name	Cam Width W1	Shutheight H1	Work Area Width W	Work Area Height H	Stroke Hw	Working Angle u (°)	Working Force F (kN)*	Weight (kg)
VACPHT140-00	VACPHT140-00	140	275	140	120	35,4	0	159,3	53
VACPHT140-10	VACPHT140-10	140	275	140	120	42,8	10	159,3	51,5
VACPHT140-20	VACPHT140-20	140	275	140	120	50,7	20	159,3	50,5
VACPHT140-30	VACPHT140-30	140	275	140	120	59,7	30	159,3	49,8
VACPHT140-40	VACPHT140-40	140	285	140	120	70,7	40	159,3	51,1
VACPHT140-50	VACPHT140-50	140	300	140	120	85,6	50	159,3	54
VACPHT140-60	VACPHT140-60	140	310	140	120	82	60	159,3	56
VACPHT140-70	VACPHT140-70	140	310	140	120	81,9	70	159,3	57,5